

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 March 2004 (11.03.2004)

PCT

(10) International Publication Number
WO 2004/021033 A1

(51) International Patent Classification⁷: **G01S 5/10**,
H04B 1/707

(21) International Application Number:
PCT/GB2003/003604

(22) International Filing Date: 18 August 2003 (18.08.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02255960.3 28 August 2002 (28.08.2002) EP

(71) Applicant (for all designated States except US): **CAM-
BRIDGE POSITIONING SYSTEMS LIMITED**
[GB/GB]; 62-64 Hills Road, Cambridge CB2 1LA (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **DUFFETT-
SMITH, Peter, James** [GB/GB]; c/o Cambridge Posi-
tioning Systems Limited, 62-64 Hills Road, Cambridge

CB2 1LA (GB). **MACNAUGHTAN, Malcolm, David**
[AU/GB]; Cambridge Positioning Systems Limited, 62-64
Hills Road, Cambridge CB2 1LA (GB). **CLARKE, John,
Christopher** [GB/GB]; Cambridge Positioning Systems
Limited, 62-64 Hills Road, Cambridge CB2 1LA (GB).
ROWE, Robert, Willem [GB/GB]; Cambridge Position-
ing Systems Limited, 62-64 Hills Road, Cambridge CB2
1LA (GB).

(74) Agent: **GILL JENNINGS & EVERY**; Broadgate House,
7 Eldon Street, London EC2M 7LH (GB).


(81) Designated States (national): CA, KR, US.

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: IMPROVEMENTS IN RADIO POSITIONING SYSTEMS



(57) Abstract: The invention provides a method of estimating the time offsets between signals transmitted by plural transmitters of a communications network and received by a receiver attached to a terminal. In the method a section of a representation of the signals from the plural transmitters received by the receiver at the terminal (a "terminal section") is created as are a first section of a representation of the signal transmitted by a first of said transmitters and a second section of a representation of the signal transmitted by a second of said transmitters. Each of the first and second sections overlaps in time with the terminal section. Using the first section, the second section and a set of signal parameters, including initial estimates of the time offsets between the first section and the terminal section and between the second section and the terminal section, a model of a section of a representation of the composite signal received by the receiver from the first and second transmitters is created. Thereafter, the model is compared with the terminal section and the set of

signal parameters including the time offset estimates is refined to minimise the difference between the model and the terminal section. The time offsets in the refined parameter set used to minimise the difference between said model and the terminal section, are adopted as the estimated time offsets between the first section and the terminal section and between the second section and the terminal section.

WO 2004/021033 A1